

# SPECIFICATIONS

# 2020 JET SKI® STX® 160X



## POWER

Engine	4-stroke, DOHC, four valves per cylinder, 4-cylinder inline
Displacement	1,498cc
Bore x Stroke	83.0 x 69.2mm
Compression Ratio	10.6:1
Induction	Naturally aspirated
Maximum Boost	N/A
Cooling System	Inducted water
Fuel System	DFI® with 60mm throttle body
Ignition	TCBI with digital advance
Starting System	Electric
Propulsion System	148mm jet pump, axial-flow, single stage
Impeller	3-blade, oval-edge stainless steel
Thrust	957 lb

## PERFORMANCE

Lubrication	Semi-dry sump system
Coupling	Direct drive from engine
Oil Capacity	5.3 qt.
Fuel Capacity	20.6 gal.
Load Capacity	496 lb.
Storage Capacity	35 gal.

## DETAILS

Overall Length	124.1 in.
Overall Width	46.5 in.
Overall Height	45.4 in.
Curb Weight	864.4 lb.
Seating Capacity	3
Color Choices	Ebony/Riptide Turquoise
Warranty	12 Month Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24, 36, or 48 months

\*\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**KAWASAKI.COM**